

Ascom d81 DECT Handset, Protector

Features

Alarm

- Push button alarm, with ability to send different alarm types
- Pull cord alarm^{1, 2}
- Man-down/No-movement alarm²
- Acoustic Location Signal (ALS)
- Automatic call after alarm

Location

- Base station location
- DECT location¹
- LF location²
- Poll location

Messaging

- Priority handling of calls and messages
- Advanced messaging queueing
- Color messaging
- 180 degrees rotation of message/call information
- Interactive messaging
- Broadcast/Multicast messaging

General

- Tough industrial handset
- IP65 classified design
- Easy registration
- Headset connector
- Wide temperature range, -10 to +55 °C
- Loud volume
- Aggressive ring signal
- Customizable sounds
- Color display
- GAP/CAP compliant DECT handset

- Dynamic output power
- Shared phone¹
- Upgradeable by license
- 18 default languages + 1 customizable
- Application controlled telephony
 - Automation calls
 - Automatic group calls
- Push to talk (PTT)
- Personalized menu
- Advanced user profiles
- System profiles
- Procedure call
- Programmable handset restrictions
- Programmable headset button
- Bluetooth and handsfree as standard
- Bluetooth barcode reader support¹



- 1. License dependent feature
- 2. Factory option

Technical Specifications

Physical

Dimensions (l × w × d):

142 × 56 × 25 mm

Weight:

170 g (battery and clip included)

Material:

Case: PC/ABS, Key pad: PC, Clip: PA

Color:

Handset: Gray/Dark Gray
Front plates: Steel Gray (standard), Dark Gray, Turquoise, Green, and Orange.

Display (w × h):

28 x 35 mm, CSTN display

Clip:

Hinge-type (standard) or swivel-type

Battery

Type:	Li-Ion
Speech time:	18 h (Bluetooth disabled/Location features disabled) 12 h (with Bluetooth headset in use/Location features disabled) 16 h (Bluetooth disabled/LF location enabled) 10 h (with Bluetooth headset in use/LF location enabled)
Stand-by time:	120 h (Black screen saver activated/Location features disabled) 60 h (Black screen saver activated/LF location enabled)
Charge time:	2 hours - 90% charged; 3 hours - fully charged.
Discharge/charge cycles:	>=80% capacity left after 400 full charge/discharge cycles.
Storage temperature: ¹	0°C to +20°C. Cool and dry place. Charged to 40% (3.7V). Even when stored under optimal conditions the battery capacity will decrease over time

Connectors

Multi-purpose connector:	For battery charging, software download, connection of headset, and configuration.
--------------------------	--

User interface

Display (w × h):	Multiple colors with high resolution, more than 65000 individual colors. 128 × 160 pixel LCD with white LED backlighting.
Indicator:	LED on top for visual indication of incoming call/message. The LED may also be used for visual indication of normal function.
Vibrator:	Incoming call/message
Buttons/Keypad:	- Soft keys (3) - Hook off key - On-hook and Power On/Off on the same key - Four-way navigation key - Numerical keys - Volume up/down buttons - Sound off key/Mute button

Audio

Ring signal:	Adjustable in 8 steps
Earpiece:	Adjustable in 8 steps
Maximum sound ring signal level:	100 dBspl @ 10 cm
Loudspeaker:	Duplex loud speaking function

Settings

Languages:	18 (Czech, Danish, German, Greek, English, Spanish, French, Italian, Magyar, Dutch, Norwegian, Polish, Portuguese (Brazilian), Russian, Slovakian, Finnish, Swedish, Turkish) + 1 customizable
------------	--

1. Note that storing Li-Ion batteries at high temperature dramatically reduces its capacity. For example storage around +60°C reduces capacity with 20% in less than a month, permanently.

Specifications are subject to change without notice.

Central Phonebook

Maximum name and number length: 40 characters in a name and 20 digits in a number

Company Phonebook

Maximum name and number length: 24 characters in a name and 24 digits in a number (1 number per name).

Entries: 1000

Local Phonebook

Contacts: - 48 character name
- 24 digit work number
- 24 digit mobile phone number
- 24 digit other number
- Selectable ring tones per contact

Entries: 250

Telephony

Indication: 14 ring signals, flashing LED and vibrator

Answer call: Button press or auto answer

Call list storage capacity: 25 calls (received, dialled and missed) with time stamp

Messaging

Maximum message length: 160 characters from handset. Message length to handset is system dependent.

Storage capacity: 30 received/sent messages (> 20 000 characters)

Radio

Receiver sensitivity: -93 dBm

Automatic DECT protocol detection: Automatic detection and configuration for US DECT and EU DECT at first registration.

Frequency range:

- EU: 1880-1900 MHz
- US: 1920-1930 MHz
- LA: 1910-1930 MHz
- BR: 1910-1920 MHz
- ---: 1900-1920 MHz

Modulation: GFSK

Channel spacing: 1.728 MHz

Antenna: Integral

Dynamic output power: EU/LA/BR: 10 mW (maximum average power)
US: 4 mW (maximum average power)

Bluetooth

Bluetooth radio spectrum: ISM 2.4000-2.4835 MHz

Environmental

Operating temperature: -10°C to +55°C

Storage temperature: -20°C to +60°C

Enclosure protection: IP65, IEC EN60529

Immunity to electromagnetic fields: 10 V/m EN61000-4-3

Specifications are subject to change without notice.

Immunity to ESD:	8 kV contact discharge and 16 kV air discharge (EN61000-4-2)
Accelerated Life Testing	
Climate stress	Handset exposed for quick temperature changes (-40° C to 75° C) 25 times. Handset dwelt on each temperature during 40 minutes.
Drop test	Handset dropped 30 times from 1,2 metres
Vibration test	Handset exposed for vibrations during 2,5 hours
Chemical stress	Handset exposed for Oleic Acid
Keypad actuation test	Keys pressed 15 000 times with a force of 13N
Squeeze test	Handset squeezed 1 000 times with a force of 130N.
Free fall test, standard product	IEC 60068-2-32, procedure 1, dropped 12 times, specification extended to 2 metres. IEC 68-2-32, procedure 2, dropped 1 000 times from 0,5 metre.
Chemical resistance test	3% Hydrochloric Acid M-alcohol (85% methylated ethanol) 60% Chlorhexidin 0.5mg/ml
Keypad abrasion test	20 NB 0500-B

Additional Features

- High quality voice
- Easy access to PBX services
- Easy replacement of handset
- Easy replaceable battery
- Mute button / Sound off key
- Local, central, and company phonebook
- Voice mail
- Sending/receiving messages (SMS)
- Centralized management
- Message acknowledgement
- Loudspeaking function
- Vibrator
- Clear call lists in charger
- Call list with the last 25 calls
- Programmable Soft/Hot keys
- Site survey tool

Accessories

- Hinge-type/Swivel-type clip
- Cover plate for no clip
- Security cord
- Pull-cord
- Leather casing, incl. swivel-type clip
- Desktop charger, Basic
- Desktop charger, Advanced
- Battery pack charger
- Charging rack
- Front plates (5 colo'rs)
- Headset with microphone on boom¹
- Headset adaptor for Mic on boom
- Peltor hearing protection headset
- ATEX/IECEx-classified headset adaptor for standard and ATEX-classified Peltor headsets


Verified Bluetooth Headsets and Bluetooth Barcode Readers

- Bluetooth Headsets
 - Nokia BH-804/BH-904
 - Plantronics Explorer 240/390/395
 - Plantronics Voyager 835/PRO/PRO+
 - Plantronics Discovery 925
 - Plantronics M20/M50/M1100
 - Jabra BT530
 - Jabra GO 660/6430/6470
 - SonyEricsson HBH-GV435/HBH-PV740
 - Peltor M2RX7-WS4
- Bluetooth Barcode Readers
 - Baracoda ScanWear BSW-L
 - Baracoda Roadrunners BRR-L
 - Baracoda Pencil2
 - Opticon OPL-2724


1. Requires the headset adaptor for Mic on boom which is ordered separately.

Specifications are subject to change without notice.



Compliance to US Regulations and Standards

Product marking:	FCC ID: BXZDH5BL,  BT QD: B016451 US: 9FVW4NANDH5 HAC
SAR (Specific Absorption Rate):	FCC/OET Bulletin 65 Supplement C and IEEE Std. 1528 / ANSI/IEEE Std. C95.1 Normal operation 0.013 W/kg (1 gram) Body worn operation 0.016 W/kg (1 gram)
Safety:	UL 60950-1
EMC/Radio:	FCC Part 15 D, and FCC Part 15 C
Hearing Aid:	47 CFR Part 68, Subpart D and TIA-968-A



Compliance to Canadian regulations and standards

Product marking:	IC: 3724B-DH5BL,  BT QD: B016451
EMC/Radio:	RSS-213 and RSS-210 (Bluetooth), ICES-003
SAR (Specific Absorption Rate):	IEEE Std C95.3 Normal operation 0.013 W/kg (1 gram) Body worn operation 0.016 W/kg (1 gram)
Safety:	CSA 60950-1
Hearing aid:	CS-03

Compliance to European regulations and standards

EU directives:	1999/5/EC (R&TTE)
Product marking:	  BT QD: B016451
Radio:	EN 301 406, TBR22
Bluetooth:	EN 300 328, EN 301489-17
SAR (Specific Absorption Rate):	EN50360 and EN62209-1, 0.137 W/kg (10 gram)
Safety:	EN60950-1
EMC:	EN301489- 6, EN 301 489-1

Compliance to Australian regulations and standards

Product marking:	  BT ID: B016451
Radio:	EN301406
Bluetooth:	EN 300 328-2, EN 301489-17, AUS/NZS-4771
SAR (Specific Absorption Rate):	EN 50360 and EN62209-1, 0.137 W/kg (10 gram)
Safety:	AUS/NZS 60950-1
EMC:	EN301489- 6, EN 301 489-1
DECT:	AS/ACIF S004

Specifications are subject to change without notice.